

PLUNGER COUPLINGS

These plunger couplings are manufactured from quality SG iron and are popular with a lot of OEM manufacturers.

Anti-rattle – adjuster screw minimises any rattle

Tough – laboratory destruction tested to 13,600kg and still operable


No Locking Pins – simply drop the plunger down

Low Maintenance – a number of manufacturers find maintenance costs are lower than with lever couplings, and last much longer

Available Drilled or Blank – available in two bolt patterns or blank (see chart below)



| PART NO | SIZE | BOLT PATTERN (AxB) | FINISH | CAPACITY |
|-----------|--------|--------------------|-------------|----------|
| TE4C788Z | 1 7/8" | Blank | Zinc Plated | 2000kg |
| TE4C788ZC | 1 7/8" | 101mm x 51mm | Zinc Plated | 2000kg |
| TE4C788ZT | 1 7/8" | Trojan 90mm x36mm | Zinc Plated | 2000kg |
| TE4C793Z | 50mm | Blank | Zinc Plated | 2000kg |
| TE4C793ZC | 50mm | 101mm x 51mm | Zinc Plated | 2000kg |
| TE4C793ZT | 50mm | Trojan 90mm x36mm | Zinc Plated | 2000kg |



LEVER COUPLINGS

TE4C794 1 7/8" CAPACITY 2000KG

CM's new 1 7/8" lever coupling (pictured) is precision cast to a quality standard. Zinc plated finish.

TE4C783 50MM* CAPACITY 2000KG

Zinc plated 50mm coupling.

* Note: the 50mm coupling is not CM brand.



TE4C794 – 1 7/8"

| PART NO | SIZE | BOLT PATTERN (AxB) | FINISH | CAPACITY |
|---------|--------|--------------------|-------------|----------|
| TE4C794 | 1 7/8" | 90mm x 36mm | Zinc Plated | 2000kg |
| TE4C783 | 50mm | 90mm x 36mm | Zinc Plated | 2000kg |

