

40MM RINGFEDER TOWING EYE

TE4C910

Weld-on type to DIN 74054 specifications.



50MM RINGFEDER TOWING EYE

TE4C914

Weld-on type to DIN 74053 specifications.

For on-road use.



40MM AGRICULTURAL TOWING EYE

TE4C930

Weld-on type to DIN 17.100 50 specifications.

For off-road use only.



50MM AGRICULTURAL TOWING EYE

TE4C934

Weld-on type.

For off-road use only.



43MM SWIVELLING AGRI TOWING EYE

TE4C940

Weld-on type.

For off-road use only.



44MM SWIVELLING AGRI TOWING EYE

TE4C945

Weld-on type.

For off-road use only.

This tow eye is manufactured from 35CrMo4 chrome moly steel.



PART NO	A	B	C	D	E	TOWING CAPACITY	DOWNWARD CAPACITY	APPLICATION
TE4C910	40mm	335mm	65mm	55mm	30.5mm	10,000kg	600kg	On-road
TE4C914	50mm	370mm	60mm	65mm	46mm	12,000kg	1,000kg	On-road
TE4C930	40mm	300mm	50mm	50mm	30mm	7000kg	1,000kg	Agricultural
TE4C934	50mm	220mm	70mm	15mm	40mm	12,000kg	900kg	Agricultural
TE4C940	43mm	278mm	57mm dia		30mm	6000kg	0kg	Agricultural
TE4C945	45mm	289mm	63mm dia		43mm	15,000kg	3,000kg	Agricultural