

**75MM FIXED RING COUPLINGS**

**TE4C790**

ADR Rating: 2270kg

Head rotates 360°

40mm thick ring section



**TE4C791**

ADR Rating: On road 3500kg  
Off road 6000kg

Can be used with a mechanical park brake lever assembly

40mm thick ring section



**PINTLE HOOKS**

**TE4C985**

On road: 5000kg capacity

Tested and complies with SAE J684



**TE4C988**

On road: 10,000kg capacity

Tested and complies with SAE J684



**TE4C989**


On road: 27,000kg capacity

Rated to SAE J684



**BOLT PATTERN**

Applies to all three pintle hooks




**3" TOWING EYE**

**TE4C959**

3" towing eye. 27000kg capacity.  
Complies with SAE J684



**BOLT PATTERN**



**1 7/8" BALL AND PINTLE HOOK**

**TE4C980**

3500kg capacity


Double locking system. Lock the hook by fitting the security pin.

Never use without the security pin in place.

Suitable for 48mm+ diameter ring eyes.



**BOLT PATTERN**




**ROCKINGER 40MM AUTOMATIC COUPLING**

**TE4C912**

Towing capacity up to 12 Tonne.  
Vertical capacity 250kg



**BOLT PATTERN**



Tested & complies with NZS5232:1993 and SAE J684

COUPLINGS