BRAKED WINCH 4:1

TE14WPB41

Winds in and winds out with no ratchet. The automatic braking system gives you full control over the load feeding in or feeding out without the need for ratchets.

Suitable for many applications.



1:1

TE14W11

A small compact winch ideal for small craft or light general winching.



3:1

TE14W31

A small compact winch for light boats up to 4.5m (14ft) and general winching.



10:1 / 5:1

TE14W1051

Heavy duty winch with twin ratio gearing for large craft and heavy winching.



BRAKED WINCH 5:1

TE14WB51

Automatic braking winch, winds in and winds out. With no ratchets to worry about, the automatic braking system gives you full control over the load feeding in or feeding out.



Suitable for many applications. Hot dip galvanised.

5:1 / 1:1

TE14W51

Medium sized winch also with direct 1:1 drive.

Robust construction for craft in the 4.5m (14ft) to 5.8m (19ft) range and general winching.



15:1 / 5:1


TE14W151

Heavy duty winch with twin ratio gearing and the capacity to handle very large craft and extra heavy winching.

Only use winch ropes with a forged safety hook.

BASE MOUNTING SPECIFICATIONS RELATES ONLY TO MODELS: TE14W11, TE14W31, TE14W1051, TE14W51, TE14W151





PART NO	RATIO	RATED LINE PULL CAPACITY	CABLE SIZE	MAXIMUM CABLE LENGTH	HANDLE LENGTH	A	В	С
TE14W11	1:1	260kg	4mm	6mtr	200mm	50mm	60mm	N/A
TE14W31	3:1	450kg	4mm	8mtr	200mm	50mm	60mm	N/A
TE14WPB41	4:1	545kg	5mm	23mtr	210mm	40mm	115mm	N/A
TE14WB51	5:1	400kg	5mm	10mtr	200mm	50mm	100mm	60mm
TE14W51	5:1/1:1	750kg	5mm	10mtr	200mm	50mm	100mm	60mm
TE14W1051	10:1/5:1	1150kg	5mm	10mtr	200mm	50mm	100mm	60mm
TE14W151	15:1/5:1	1650kg	6mm	10mtr	200mm	50mm	100mm	60 mm