

## WIRE ROPE\*

4mm and 5mm winch wires are supplied complete with galvanised thimble and stainless steel 'S' hook.

6mm winch wires are supplied with a galvanised thimble and forged safety hook.



\* Note: 6mm are the only ropes suitable for car transporter trailers. A rated Dee Shackle must be used.

PART NO	WIRE DIAMETER	WIRE LENGTH	CAPACITY	FOR USE WITH WINCH
TE14WW4-6	4mm	6mtr	600kg	1:1, 3:1 & 5:1
TE14WW5-6	5mm	6mtr	1000kg	5:1
TE14WW5-75	5mm	8mtr	1000kg	10:1
TE14WW6-75*	6mm	8mtr	1500kg	15:1

## SYNTHETIC ROPE\*

CM manual winch ropes are made from a special high-strength synthetic material. No more rusting wire or metal splinters in the hands, these ropes are easy to fit.

### TE14WR5 TE14WR6

Fitted with Stainless Steel 'S' Hook



### TE14WR7 TE14WR8

Fitted with Cast Iron Hook & Safety Catch



PART NO	ROPE LENGTH	CAPACITY	FOR USE WITH WINCH
TE14WR5	5mtr	1000kg	1:1 & 3:1
TE14WR6	6mtr	1500kg	5:1
TE14WR7	7mtr	1500kg	10:1
TE14WR8	8mtr	2500kg	15:1

## NYLON STRAP\*

Polyester seat belt type webbing, prevents crossover when laying onto drum. Stainless steel 'S' hook one end, 4mm wire rope tail on other end for drum attachment.



PART NO	WEB WIDTH	WEB LENGTH	CAPACITY
TE14WS25-3	25mm	3mtr	1500kg
TE14WS25-4	25mm	4mtr	1500kg
TE14WS25-5	25mm	5mtr	1500kg
TE14WS25-6	25mm	6mtr	1500kg
TE14WS50-3	50mm	3mtr	1500kg
TE14WS50-4	50mm	4mtr	1500kg
TE14WS50-5	50mm	5mtr	1500kg
TE14WS50-6	50mm	6mtr	1500kg

## CAST ROPE HOOK

### TE14WWCH

2500kg maximum line pull capacity.



## STAINLESS STEEL 'S' HOOK 11MM

### TE14WWS

1400kg maximum line pull capacity.

