


SINGLE-LEAF MARINE QUALITY SPRINGS

Parabolic tapered single leaf springs are ideal for fitting to all trailers used in marine applications. Being a single leaf eliminates the risk of salt water corrosion between the leaves. The 45mm wide are galvanised and the 51mm are finished in an enamel grey paint.



U-Bolt Kit sold separately

PART NO	CAPACITY PER PAIR	A	B	C	EYE DIAMETER	WIDTH	FINISH
TE7P1000	1000kg	350mm	410mm	170mm	½"	45mm	Galvanised
TE7P1400	1400kg	350mm	410mm	170mm	½"	45mm	Galvanised
TE7S0500	500kg	330mm	430mm	100mm	16mm	51mm	Painted
TE7S1000	1000kg	330mm	430mm	100mm	16mm	51mm	Painted
TE7S1500	1500kg	330mm	430mm	100mm	16mm	51mm	Painted
TE7S2000	2000kg	330mm	430mm	100mm	16mm	51mm	Painted



SPRING INSTALLATION

MATT'S TOP TIP: "Tighten U-bolts sufficiently and again after the first 100km of use"

There must be zero flex around the centre bolt area of spring leaves, as this is the weakest point of the spring. Any flexing in this area can cause the leaves to fracture across the centre bolt hole. To eliminate any flexing in this area, the U-bolts must be sufficiently tightened to clamp the spring between the axle beam and fish plate. U-bolts must also be retightened after the first 100km of use.