

LED ECU WIRING HARNESS

TE17AH17

The inline Harness eliminates pulse interference commonly found on modern European vehicle electrics, which interfere with LED lighting on trailers. Simply install between the trailer connector and vehicle wiring.



LED TRAILER LIGHT INTERFACE

In line adaptor to prevent faults and flashing caused by trailers with LED lamps.

5 amps maximum power output per channel. 12 volts compatible only.

Can be used with bulbs as well as LEDs, however because there should be no reason to use these when the trailer has bulbs, it is not recommended.

Waterproof.

TE17LTI7-7

7-PIN FLAT PLUG TO 7 PIN FLAT SOCKET.



TE17LTI13-7

13-PIN ROUND EUROPEAN PLUG TO 7-PIN FLAT SOCKET



LED FLASHER LOAD RESISTOR

TE17LTR12

Removes fault codes associated with LED lamps on vehicles with inbuilt bulb monitoring.

- 3 separate 21 watt loads.
- 12 volt.
- Waterproof.
- 120mm x 36mm x 30mm.



JUNCTION BOX

TE17JB1

135mm (l) x 102mm (w) x 38 (h)

8 way weather-proof junction box.

Constructed of electrically insulated rubber with transparent cover for easy inspection.

4 cable entry points – can be cut to size to suit various cable diameters.

